

C177B Oil Change Procedure

Tools and Supplies Needed:

Crescent wrench
3/8 socket and 3/8 end wrench
Wire wrap tool and wire
Phillips screwdriver and Phillips stubby
Wire cutter
Oil drain pan
Funnel
Rags
Container for screws
Punch
Headlamp
Four hands (reinstalling the cowl is a two-person job)

Procedure:

1. Warm the engine oil. A quick flight to the "Y" and back is an efficient way to do this. High power ground runs are not recommended.
2. Remove Cowl:
 - a. Remove screws connecting the fronts of the cowl halves. Note location of screws with white plastic washers.
 - b. Undo all ¼ turn fasteners on top cowl. These fasteners run along the joint with the lower cowl on both sides, and along the firewall at the back.
 - c. Lift the top cowl off and set aside.
 - d. Locate the landing light wires on the left side of the engine compartment. There are two bullet connectors that you should find secured with a zip tie. Remove the zip tie and disconnect the leads.
 - e. Disconnect the cowl flap pushrods from the cowl flaps. Put the fasteners back in place on the disconnected pushrods to prevent losing them.
 - f. Undo the ¼ turn fasteners that secure the lower cowl to the firewall. This requires two people. Someone should support the cowl while the fasteners are undone.
 - g. Set the lower cowl aside.
3. Drain the oil:
 - a. Place a bucket underneath the oil drain hose at the bottom of the oil sump.
 - b. Open the quick drain valve to start the oil draining. (twist and push per the diagram on the valve.)
 - c. Note how the blue anodized oil cooler drain cap is safety wired so that you can correctly replace the wire when the cap is reinstalled. The cap is on the right side of the engine compartment.
 - d. Remove the safety wire on oil cooler drain cap. Place a catch pan underneath the oil cooler drain and remove the cap to drain the oil from the cooler.
 - e. To expedite draining, punch a hole in the oil filter to allow air into the system.
 - f. Allow all the oil to drain completely from the oil cooler and the engine sump.

